

ZY909

4inch Shipping Label Printer

Features

- Automatic induction, positioning test
- Professional wear-resistant print head, designed for printing
- Stable performance, high-speed and clear printing
- It can print continuously for every day.
- Ribbon-free, ribbon-free, ink-free
- Worry-free printing, mobile phones and small programs can print easily.



High definition printing



Self-Inspection



Error alert



Big font



High printing



Rotating screen



Model	ZY909
Print Method	Direct Thermal
Resolution	203dpi(8dots/mm)
Printing Width	108mm (4.25")
Interface	U/U+L
Print Speed	152 mm(6")/s Max.
Fonts	
Font A	12x24
Font B	9x17
Chinese	GB18030, BIG5 24x24dots
Japanese/Korea	Optional
Internal fonts	8MB Flash Memory/8MB SDRAM
Barcode	
1D	Code 39, Code 93, Code 128UCC, Code 128, subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D	PDF-417, Maxicode, DataMatrix, QR code
Power Supply	
Input	AC 100V-240V 50/60HZ
Output	DC 24V/2.5A
Detection	
Sensors	Thermal sensitive resistance
Paper exists detection	Photoelectric sensor

Paper

Paper Type	Thermal Receipt Paper/Thermal Label Paper
Paper Width	25.4-110mm
Paper Thickness	0.25mm
Roll inner Diameter	Max. Ø 25mm
Paper off	Tear off

Physical Characteristics

Working Condition	5~40°C(41~104°F)Humidity: 25 ~ 85% non-condensing
Storage Condition	-40°C-60°C(-41~140°F)Humidity: 10 ~ 90% non-condensing
Dimensions	196.5(D)x115.5(W)x104.5(H)mm
Weight	1.146kg

Performance Features

Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM

Reliability

Warranty	12 months
Printing head	50 km

Accessories

Accessories	Data cable, power adaptor, power cord , manual,Label holder,CD
-------------	--

Packing

Individual box	Dimension265×175×172mm(LXWXH)1unit/box
Master carton	Dimension595×350×515mm(LXWXH)12unit/carton

OS

Emulation	TSPL/EPL
Driver	Windows XP /Win7/Win8 /Win10/Win11
SDK	Android, IOS